

Product Code

Home / High Frequency Driver / PTS440

New

PTS440

HIGH FREQUENCY DRIVER

1.75 Inches

PRO SPL

8Ω



Compare



Diaphragm Material Mylar
Voice Coil Diameter 44 mm 1.75 in
Continuous Power Handling 250 W

Product Code



Specifications

Parameters

Design

Mounting and Shipping Info

Specifications

Nominal Diameter	44 mm (1.75 in)
Nominal Power Handling	125 W ⓘ
Sensitivity	106 dB ⓘ
Recommended Crossover	2.4 kHz
Winding Material	Aluminum
Flux Density	1.65 T
Nominal Impedance	8 Ω
Continuous Power Handling	250 W ⓘ
Frequency Range	2.4 kHz - 20 kHz ⓘ
Voice Coil Diameter	44 mm (1.75 in)
Winding Depth	2.7 mm (0.11 in)
Diaphragm Material	Mylar



Product Code



Re

4.5 Ω

Design

Cone Shape

Planar

Cone Material

Mylar

Connection Type

Faston

Mounting and Shipping Info

Overall Diameter

99 mm (4 in)

Baffle Cutout Diameter

85 mm (3.35 in)

Flange and Gasket Thickness

4 mm (0.16 in)

Shipping Units

12 pcs

Bolt Quantity

4 pcs



Product Code

Depth	42 mm (1.65 in)
-------	-----------------

Net Weight	0.8 kg (1.76 lb)
------------	------------------

Basket Material	Aluminum
-----------------	----------

Bolt Diameter	4 mm
---------------	------

info@ciare.com



SOUND & VISION

a division of the B&C SPEAKERS Group

Eighteen Sound srl

via A. Botticelli, 10

42124 Reggio Emilia

ITALY

VAT # IT 02577810357

HOME

PRODUCTS

ABOUT US

SUPPORT

Product Code



[Privacy](#) | [Cookie](#) | [Terms of use](#)

Dinamo

