

LF Loudspeakers

FTR18-4080HDX

18-inch, cast aluminium chassis, ferrite magnet
LF driver

- Glass loaded paper cone with weather-resistant impregnation
- Optimised double suspension
- Airflow vented magnet assembly for dynamic heat dispersion

2000W

Continuous
power rating

95dB

sensitivity

4in

Round copper
voice coil

General Specifications

Nominal Diameter	457mm / 18in
Power Rating	1000W
Continuous power rating	2000W
Rated impedance	8 ohm
Sensitivity	95dB
Frequency range	30-2500Hz
Chassis type	Cast aluminium
Magnet type	Ferrite
Magnet weight	3.1kg / 110oz
Voice coil diameter	100mm / 4in
Voice coil material	Round copper
Former material	Glass fibre
Cone material	Glass loaded paper (weather-resistant)
Surround material	Cloth-sealed
Suspension	Double
Gap height (Hg)	9.5mm / 0.37in
VC winding height (Hvc)	25mm / 0.99in

Parameters

Sd	1134.12cm ² / 175.79in ²
Fs	39.20Hz
Mms	171.75g / 6.06oz
Qms	5.387
Qes	0.466
Qts	0.429
Re	5.00 ohm
Vas	174.88l / 6.18ft ³
Bl	21.29Tm
Cms	0.10mm/N
Rms	7.85kg/s
Le (at 1kHz)	1.79mH
Xmax	10.1mm / 0.4in

Packed Dimensions & Weight


Single pack size W x D x H	500mm x 500mm x 240mm / x 19.7in 19.7in x 9.4in
Single pack weight	11.6kg / 25.6lb
Multi pack qty	24
Multi pack size W x D x H	1210mm x 1050mm x 980mm / 47.6in x 41.3in x 35.4in
Multi pack weight	278kg / 608lb



Mounting Information

Overall diameter	452mm / 17.8in
Overall depth	205mm / 8.1in
Cut-out diameter	416mm / 16.38in
Mounting hole dimensions	10x7mm / 0.4x0.27in
Number of mounting holes	8
Mounting hole PCD	429-440mm / 16.89-17.32in
Unit weight	9.8kg / 21.6lb

Frequency Response and Impedance Curves



Power rating: Tested for two hours using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance. Loudspeaker tested in free air.

Continuous power rating: Defined as 3dB greater than the AES rating.

Sensitivity: Measured on axis at 1W, 1m in 2? anechoic environment.

Parameters: Measured after unit subjected to pre-conditioning signal.

Xmax: 0.5*(Hvc-Hg) + 0.25*Hg