

DE12 8 Ω

SPECIFICATIONS

Driver mounted on B&C ME 45 horn.

Throat Diameter	25 mm (1 in)
Nominal Impedance	8 Ω
Minimum Impedance	7.8 Ω
Nominal Power Handling	25 W
2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance.	
Continuous Power Handling	50 W
Power on Continuous Program is defined as 3 dB greater than the Nominal rating.	
Sensitivity	106 dB
Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.	
Frequency Range	1.5 kHz - 18 kHz
Recommended Crossover	2.2 kHz
12 dB/oct. or higher slope high-pass filter.	
Voice Coil Diameter	36 mm (1.4 in)
Winding Material	Aluminium
Inductance	0.14 mH
Flux Density	1.45 T
Diaphragm Material	Mylar

MOUNTING AND SHIPPING INFO

Two M5 holes 180° on 76 mm (3 in) diameter

Overall Diameter	90 mm (3.5 in)
Depth	49 mm (2 in)
Net Weight	1.05 kg (2.31 lb)
Shipping Units	1 pcs
Shipping Weight	1.08 kg (2.38 lb)
Shipping Box	105x105x65 mm (4.13x4.13x2.56 in)



SERVICE KITS

HF replacement-diaphragm	MMD0128
--------------------------	----------------

- 50 W continuous program power capacity
- 1" horn throat diameter
- 36 mm (1.4 in) aluminium voice coil
- Polyester diaphragm
- 1500 - 18000 Hz response
- 106 dB sensitivity



DE12 8 Ω



DE12 8 Ω

